

Cross-link 82° Countersinks

- 3 in 1 Tool: Spot, Drill & Countersink for English flat head screws
- Extreme-performance in aluminum applications
- Patent Pending design



82° Angle									Speeds & Feeds	
Part No		English Screw	Drill Diameter	Drill Length	Body Diameter	Shank Diameter	Shank Length	Overall Length	SFM	FEED - IPR
Cobalt	Alu Coating									
55-CO-289	CO-AL-289	#5	.141	7/16	7/16	7/16	FULL	4	300-700	0.002
55-CO-290	CO-AL-290	#6	.154	7/16	7/16	7/16	FULL	4	300-700	0.002
55-CO-291	CO-AL-291	#8	.180	7/16	7/16	7/16	FULL	4	300-700	0.003
55-CO-292	CO-AL-292	#10	.206	7/16	7/16	7/16	FULL	4	300-700	0.003
55-CO-293	CO-AL-293	#12	.234	7/16	1/2	1/2	FULL	4	300-700	0.004
55-CO-294	CO-AL-294	1/4	.266	5/8	1/2	1/2	FULL	4	300-700	0.004
55-CO-295	CO-AL-295	5/16	.328	3/4	11/16	1/2	2.225	4	300-700	0.006
55-CO-296	CO-AL-296	3/8	.391	3/4	13/16	1/2	2.225	4	300-700	0.008
55-CO-297	CO-AL-297	1/2	.516	1	1	1/2	2.375	4-1/2	300-700	0.010